

Мощность в ваттах [W]	Напряжение в вольтах [V]	Цоколь	Наименование	Код продукта	Св. поток [лм]	ССТ [К]	CRI [Ra]	Срок службы [ч]	Диаметр [мм]	Длина [мм]	ЕЭС	К-во в упаковке
-----------------------	--------------------------	--------	--------------	--------------	----------------	---------	----------	-----------------	--------------	------------	-----	-----------------

ViaX™ S 2-pin, встроенный стартер

5	35	G23	F5BX/SPX27/827	37654	265	2700	82	10,000	32	107.5	A	10
5	35	G23	F5BX/SPX41/840	37661	265	4000	82	10,000	32	107.5	A	10
7	47	G23	F7BX/SPX27/827	37846	425	2700	82	10,000	32	136.5	A	10
7	47	G23	F7BX/830	38930	425	3000	82	10,000	32	136.5	A	10
7	47	G23	F7BX/SPX35/835	37659	425	3500	82	10,000	32	136.5	A	10
7	47	G23	F7BX/SPX41/840	37660	425	4000	82	10,000	32	136.5	A	10
7	47	G23	F7BX/865	38984	425	6500	82	10,000	32	136.5	A	10
9	60	G23	F9BX/827	37651	600	2700	82	10,000	32	167	A	10
9	60	G23	F9BX/830	38929	600	3000	82	10,000	32	167	A	10
9	60	G23	F9BX/SPX35/835	37652	600	3500	82	10,000	32	167	A	10
9	60	G23	F9BX/SPX41/840	37653	600	4000	82	10,000	32	167	A	10
9	60	G23	F9BX/865	38985	600	6500	82	10,000	32	167	A	10
11	91	G23	F11BX/827	37663	900	2700	82	10,000	32	237	A	10
11	91	G23	F11BX/830	38928	900	3000	82	10,000	32	237	A	10
11	91	G23	F11BX/835	37666	900	3500	82	10,000	32	237	A	10
11	91	G23	F11BX/840	37664	900	4000	82	10,000	32	237	A	10
11	91	G23	F11BX/865	38986	900	6500	82	10,000	32	237	A	10



ViaX™ S/E 4-pin, требуется внешний стартер

5	35	2G7	F5BX/827/4P	37714	265	2700	82	10,000	37.5	92	A	10
5	35	2G7	F5BX/840/4P	37715	265	4000	82	10,000	37.5	92	A	10
7	47	2G7	F7BX/827/4P	37658	425	2700	82	10,000	37.5	121	A	10
7	47	2G7	F7BX/840/4P	37716	425	4000	82	10,000	37.5	121	A	10
9	60	2G7	F9BX/827/4P	37710	600	2700	82	10,000	37.5	151	A	10
9	60	2G7	F9BX/840/4P	37711	600	4000	82	10,000	37.5	151	A	10
11	91	2G7	F11BX/827/4P	37717	900	2700	82	10,000	37.5	222	A	10
11	91	2G7	F11BX/840/4P	37713	900	4000	82	10,000	37.5	222	A	10
11	91	2G7	F11BX/865/4P	12603	900	6500	82	10,000	37.5	222	A	10



ViaX™ D 2-pin, встроенный стартер

10	64	G24D-1	F10DBX/T3/827/2P	78211	600	2700	82	12000	34.4	108	B	10
10	64	G24D-1	F10DBX/T3/830/2P	78212	600	3000	82	12000	34.4	108	B	10
10	64	G24D-1	F10DBX/T3/835/2P	78213	600	3500	82	12000	34.4	108	B	10
10	64	G24D-1	F10DBX/T3/840/2P	78214	600	4000	82	12000	34.4	108	B	10
10	64	G24D-1	F10DBX/T3/865/2P	78215	600	6500	82	12000	34.4	108	B	10
13	91	G24D-1	F13DBX/T3/827/2P	78221	900	2700	82	12000	34.4	139	A	10
13	91	G24D-1	F13DBX/T3/830/2P	78222	900	3000	82	12000	34.4	139	A	10
13	91	G24D-1	F13DBX/T3/835/2P	78223	900	3500	82	12000	34.4	139	A	10
13	91	G24D-1	F13DBX/T3/840/2P	78224	900	4000	82	12000	34.4	139	A	10
13	91	G24D-1	F13DBX/T3/865/2P	78225	900	6500	82	12000	34.4	139	A	10
18	100	G24d-2	F18DBXT4/SPX27/827	12860	1200	2700	82	12,000	34.4	154	B	10
18	100	G24d-2	F18DBXT4/SPX30/830	12861	1200	3000	82	12,000	34.4	154	B	10
18	100	G24d-2	F18DBXT4/SPX35/835	12863	1200	3500	82	12,000	34.4	154	B	10
18	100	G24d-2	F18DBXT4/SPX41/840	12864	1200	4000	82	12,000	34.4	154	B	10
18	100	G24d-2	F18DBXT4/SPX65/865	13017	1200	6500	82	12,000	34.4	154	B	10
26	105	G24d-3	F26DBXT4/SPX27/827	35250	1800	2700	82	12,000	34.4	169.5	B	10
26	105	G24d-3	F26DBXT4/SPX30/830	35237	1800	3000	82	12,000	34.4	169.5	B	10
26	105	G24d-3	F26DBXT4/SPX35/835	35251	1800	3500	82	12,000	34.4	169.5	B	10
26	105	G24d-3	F26DBXT4/SPX41/840	35252	1800	4000	82	12,000	34.4	169.5	B	10
26	105	G24d-3	F26DBXT4/SPX65/865	35305	1630	6500	82	12,000	34.4	169.5	B	10

